



Specifications

Thermal efficiency	
U _w *: Coefficient value for reference design	6,1 W/m ² K
*:	reference window 1230 x 1480 mm, basic glass for a given series
Profile	
Profile name:	DA-45
Installation depth:	Sash: 45 mm Frame: 54 mm
Number of chambers:	1
Thermal break:	none
Number of seals:	Two seals of two-component EPDM synthetic rubber
Glass	
Glazing package:	Float 4 mm
U _g value:	5,8 W/m ² K
Package thickness:	4 to 34 mm
Sound insulation of available glazing:	R _w : 31 to 42 dB

Fitting	
Type:	---
Hinges:	surface-mounted
Anti-Theft protection:	anti-theft latch
Micro-ventilation:	yes
Other:	Four-stage tilt and slide mechanism Handle rotation lock with a lifter
Handle	
Colours:	---
Handle model:	1006
Dimensions	
Maximum window width - single sash:	1600 mm
Maximum window height - single sash:	2400 mm
Maximum window width - double sash with a movable post:	3000 mm
Maximum window height - double sash with a movable post:	2400 mm
Maximum sash area:	3 m ²
Maximum size of fixed glazing (when using a special glass, maximum area of 7 m ² and weight of 250 kg):	3500 x 2900 mm or 2900 x 3500 mm

Photos

