



## Specifications

Thermal efficiency	
U <sub>w</sub> *: Coefficient value for reference design	1,3 W/m <sup>2</sup> K
*:	reference window 1230 x 1480 mm, basic glass for a given series
Profile	
Profile name:	DA-65EF
Installation depth:	Frame: 65 mm   Sash: 74 mm
Number of chambers:	3
Thermal break:	Thermal breaks 30 mm made of fiber glass reinforced by polyamide
Number of seals:	Two seals of two-component EPDM synthetic rubber
Glass	
Glazing package:	4/18/4/18/4
U <sub>g</sub> value:	0,5 W/m <sup>2</sup> K
Package thickness:	13 to 60 mm

Sound insulation of available glazing:	Rw: 31 to 47 dB
<b>Fitting</b>	
Type:	---
Hinges:	surface-mounted
Anti-Theft protection:	anti-theft latch
Micro-ventilation:	yes
Other:	Four-stage tilt and slide mechanism   Handle rotation lock with a lifter
<b>Handle</b>	
Colours:	---
Handle model:	1006
<b>Dimensions</b>	
Maximum window width – single sash:	1600 mm
Maximum window height – single sash:	2400 mm
Maximum window width – double sash with a movable post:	3200 mm
Maximum window height – double sash with a movable post:	2400 mm
Maximum sash area:	3 m <sup>2</sup>
Maximum size of fixed glazing (when using a special glass, maximum area of 7 m <sup>2</sup> and weight of 250 kg):	3500 x 2900 mm or 2900 x 3500 mm

## Photos

