



Specifications

Thermal efficiency	
U _w *: Coefficient value for reference design	1,3 W/m ² K
*:	reference window 1230 x 1480 mm, basic glass for a given series
Profile	
Profile name:	DA-65EFUS
Installation depth:	Frame: 65 mm Sash: 74 mm
Number of chambers:	3
Thermal break:	Thermal breaks 30 mm made of fiber glass reinforced by polyamide
Number of seals:	Two seals of two-component EPDM synthetic rubber
Glass	
Glazing package:	1,3 W/m ² K
U _g value:	1,0 W/m ² K
Package thickness:	24 to 30 mm

Sound insulation of available glazing:	---
Fitting	
Type:	---
Hinges:	concealed
Anti-Theft protection:	anti-theft latch
Micro-ventilation:	yes
Other:	Four-stage tilt and slide mechanism Handle rotation lock with a lifter
Handle	
Colours:	---
Handle model:	1006
Dimensions	
Maximum window width – single sash:	1250 mm
Maximum window height – single sash:	2200 mm
Maximum window width – double sash with a movable post:	3000 mm
Maximum window height – double sash with a movable post:	2200 mm
Maximum sash area:	3 m ²
Maximum size of fixed glazing (when using a special glass, maximum area of 7 m ² and weight of 250 kg):	3500 x 2900 mm or 2900 x 3500 mm

Photos

