



Specifications

Thermal efficiency	
U _w *: Coefficient value for reference design	0,8 W/m ² K
*:	reference window 1230 x 1480 mm, basic glass for a given series
Profile	
Profile name:	DA-70
Installation depth:	Sash: 80,8 mm Frame: 77 mm
Number of chambers:	4
Thermal break:	43 mm thermal breaks made of glass-fibre reinforced polyamidem
Number of seals:	Three seals made of two-component EPDM synthetic rubber
Glass	
Glazing package:	4x18x4x18x4, black warm edge spacer bar
U _g value:	0,5 W/m ² K
Package thickness:	15 to 60 mm
Sound insulation of available glazing:	R _w : od 31 to 47dB
Fitting	
Type:	---

Hinges:	surface-mounted (optional: concealed hinges)
Anti-Theft protection:	anti-theft latch
Micro-ventilation:	yes
Other:	Handle rotation lock with lifter
Handle	
Colours:	Standard colour: white, brown, silver Optional colour: stainless steel, old gold, joinery colour
Handle model:	Made of aluminium
Dimensions	
Maximum window width - single sash:	1700 mm
Maximum window height - single sash:	2800 mm
Maximum window width - double sash with a movable post:	3400 mm
Maximum window height - double sash with a movable post:	2800 mm
Maximum sash area:	3 m ²
Maximum size of fixed glazing (when using a special glass, maximum area of 7 m ² and weight of 250 kg):	3500 x 2900 mm or 2900 x 3500 mm

Photos

