



Specifications

Thermal efficiency	
U _w *: Coefficient value for reference design	0,8 W/m ² K
*:	U _w of windows with sash dimensions 2000 x 1100 mm with 2-chamber glass U _g 0.5 W/(m ² K), with warm distance frame and fire protection glass in EI30 class.
Profile	
Profile name:	DA-77
Installation depth:	Sash: 86 mm Frame: 77 mm
Number of chambers:	4
Thermal break:	43 mm thermal breaks made of glass-fibre-reinforced polyamide
Number of seals:	Two seals made of two-component EPDM synthetic rubber
Glass	
Glazing package:	5T ESG /12+A/5TESG/12+A/EI 30
U _g value:	0,7 W/m ² K
Package thickness:	41 to 60 mm
Sound insulation of available glazing:	R _w : 31 to 42 dB
Fitting	

Type:	---
Hinges:	surface-mounted (optional: concealed hinges)
Anti-Theft protection:	anti-theft latch
Micro-ventilation:	yes
Other:	Handle rotation lock with lifter
Handle	
Colours:	Standard colour: white, brown, silver Optional colour: stainless steel, old gold, joinery colour
Handle model:	With a key, made of aluminium
Dimensions	
Maximum window width - single sash:	1600 mm
Maximum window height - single sash:	2400 mm
Maximum window width - double sash with a movable post:	3200 mm
Maximum window height - double sash with a movable post:	2400 mm
Maximum sash area:	3 m ²
Maximum size of fixed glazing (when using a special glass, maximum area of 7 m ² and weight of 250 kg):	3500 x 2900 mm or 2900 x 3500 mm
Other	
Other:	automatic drives for turn and tilt windows

Photos

