

DA-77C opening outwards



Specifications

Thermal efficiency	
U _w *: Coefficient value for reference design	0,9 W/m ² K
*:	Glass 4/18/4/18/4 window size 48 7/16 in x 58 4/16 in (1230 mm x 1480 mm)
Profile	
Profile name:	DA-77C
Installation depth:	Frame 77 mm Sash 86 mm
Number of chambers:	4
Thermal break:	Thermal spacers 43 and 42 mm
Number of seals:	Three seals of two-part EPDM synthetic rubber
Glass	
Glazing package:	4/18/4/18/4 warm spacer bar
U _g value:	0,5 W/m ² K
Package thickness:	frame - from 13 to 61 mm, sash- from 22 to 70 mm
Sound insulation of available glazing:	R _w : from 31 to 47dB
Fitting	
Type:	---

Hinges:	scissor (invisible) or traditional turn-and-tilt hinges (visible)
Anti-Theft protection:	---
Micro-ventilation:	---
Other:	---
Handle	
Colours:	White, Chrome, Chrome Matt
Handle model:	Virage (shand)
Dimensions	
Maximum window width - single sash:	1400 mm
Maximum window height - single sash:	2500 mm
Maximum window width - double sash with a movable post:	solution not available in the system
Maximum window height - double sash with a movable post:	solution not available in the system
Maximum sash area:	3 m ²
Maximum size of fixed glazing (when using a special glass, maximum area of 7 m2 and weight of 250 kg):	solution not available in the system
Technical parameters	
Water tightness:	Class 4, PN-EN 12207:2001
Air permeability:	Class E1350, PN-EN 12208:2001
Wind load resistance:	up to class C5/B5, PN-EN 12210:2001

Photos

