

## DA-90 Thermo corner solution



## Specifications

Thermal efficiency	
U <sub>w</sub> *: Coefficient value for reference design	0,80 W/m <sup>2</sup> K
*:	reference window 1230 x 1480 mm
Profile	
Profile name:	DA-90 Thermo
Installation depth:	Sash: 99 mm   Frame: 90 mm
Number of chambers:	3
Thermal break:	45 mm thick glass fibre reinforced polyamide, additional insulating insert in the middle chamber
Number of seals:	Two EPDM two-component synthetic rubber seals
Glass	
Glazing package:	4X18x4x18x4
U <sub>g</sub> value:	0,5 W/m <sup>2</sup> K
Package thickness:	from 21 to 67 mm
Sound insulation of available glazing:	R <sub>w</sub> : from 31 to 47 dB

Fitting	
Type:	n/a
Hinges:	n/a
Anti-Theft protection:	n/a
Micro-ventilation:	n/a
Other:	Handle rotation lock with lifter
Handle	
Colours:	---
Handle model:	1006
Sash size	
Min. sash width:	560 mm x 560 mm x 560 mm
Max. sash width:	2400 mm x 3000 mm x 3000 mm
Min. sash height:	560 mm x 560 mm x 560 mm
Max. sash height:	2400 mm x 3000 mm x 3000 mm
Max. sash weight:	---
Max. sash area:	---

## Photos

