



Specifications

Thermal efficiency	
U _w *: Coefficient value for reference design	1,1 W/m ² K
*:	reference construction 2460 mm x 2180 mm
Profile	
Profile name:	DA-77
Installation depth:	Sash: 77 mm Frame: 174 mm
Number of chambers:	3
Thermal break:	Thermal breaks 35 mm made of fiber glass reinforced by polyamide
Number of seals:	Two seals of two-component EPDM synthetic rubber
Glass	
Glazing package:	4x18x4x18x4
U _g value:	0,5 W/m ² K
Package thickness:	from 14 to 58 mm
Sound insulation of available glazing:	R _w : from 31 to 47dB
Fitting	
Type:	Lift -sliding fittings

Hinges:	n/a
Anti-Theft protection:	n/a
Micro-ventilation:	yes
Other:	n/a
Handle	
Colours:	Standard color: white, brown, silver Optional color: stainless steel, old gold, colour of ironwork
Handle model:	Made of aluminium
Maximum construction dimensions	
Width:	6500 mm
Height:	3000 mm
Sash size	
Min. sash width:	900 mm
Max. sash width:	3300 mm
Min. sash height:	1900 mm
Max. sash height:	3200 mm
Max. sash weight:	300 kg
Max. sash area:	---
Other	
Other:	OPTION: Automatic door - remote-controlled door opening and closing

Photos

