



Specifications

Thermal efficiency	
U _w *: Coefficient value for reference design	1,4 W/m ² K
*:	reference construction 2460 mm x 2180 mm
Profile	
Profile name:	DA-51
Installation depth:	Sash: 51 mm Frame: double track - 118 mm; double track with the optional flooding threshold - 125 mm; three-track: 184 mm; three-track with the option of a threshold to be flooded - 192 mm; monorail - 142 mm
Number of chambers:	3
Thermal break:	26 mm glass-fibre reinforced polyamide thermal breaks
Number of seals:	Two EPDM dual-component synthetic rubber seals
Glass	
Glazing package:	Triple glazing package: 4ESG/12Ar/4ESG/12Ar/4ESG TGI frames
U _g value:	0,7 W/m ² K
Package thickness:	glazing thickness available: from 8 to 36 mm permanent fields in monorail constructions from 20 mm to 60 mm
Sound insulation of available glazing:	---
Fitting	
Type:	Lift - sliding fitting
Hinges:	n/a
Anti-Theft protection:	n/a
Micro-ventilation:	yes
Other:	n/a
Handle	
Colours:	---
Handle model:	Made of aluminium

Maximum construction dimensions

Width:	6500 mm
--------	---------

Height:	2600 mm
---------	---------

Sash size

Min. sash width:	710 mm
------------------	--------

Max. sash width:	2000 mm
------------------	---------

Min. sash height:	1750 mm
-------------------	---------

Max. sash height:	2600 mm
-------------------	---------

Max. sash weight:	200 kg
-------------------	--------

Max. sash area:	---
-----------------	-----