



Specifications

Thermal efficiency	
U _w *: Coefficient value for reference design	1,2 W/m ² K
*:	doors reference 1230 mm x 2180 mm
Profile	
Profile name:	DA-77
Installation depth:	Sash: 77 mm Frame: 77 mm
Number of chambers:	4
Thermal break:	31 mm glass-fibre reinforced polyamide thermal breaks
Number of seals:	Two EPDM dual-component synthetic rubber seals
Glass	
Glazing package:	Triple glazing package 33,1x18x4x18x33,1
U _g value:	0,5 W/m ² K
Package thickness:	glazing thickness available: from 14 to 58 mm
Sound insulation of available glazing:	---
Fitting	
Type:	---
Hinges:	SURFACE HINGES Durable and stable hinges adjustable in three planes. They guarantee smooth door operation and increase safety. Standard color: white, brown, silver Optional colors: Joinery color
Anti-Theft protection:	---
Micro-ventilation:	---
Other:	---
Handle	
Colours:	Standard color: white, brown, silver
Handle model:	Handle on a long backplate made of high quality aluminum.
Insert	

Insert type:	Construction insert
Lock	
Lock type:	1-point locking system with a classic latch-bolt mechanism
Sash size	
Min. sash width:	900 mm
Max. sash width:	1400 mm
Min. sash height:	2050 mm
Max. sash height:	3000 mm
Max. sash weight:	180 kg
Max. sash area:	---