

Profiled Doors DA-45 (internal system)



Specifications

Thermal efficiency	
Uw*: Coefficient value for reference design	6,0 W/m ² K
*:	doors reference 1230 mm x 2180 mm
Profile	
Profile name:	DA-45
Installation depth:	Sash: 45 mm Frame: 45 mm
Number of chambers:	1
Thermal break:	none
Number of seals:	Two EPDM dual-component synthetic rubber seals
Glass	
Glazing package:	Single 33,1 mm
Ug value:	5,7 W/m ² K
Package thickness:	Glazing thickness available from 4 to 25 mm
Sound insulation of available glazing:	---
Fitting	
Type:	---
Hinges:	SURFACE HINGES Durable and stable hinges adjustable in three planes. They guarantee smooth door operation and increase safety. Standard color: white, brown, silver Optional colors: Joinery color
Anti-Theft protection:	---
Micro-ventilation:	---
Other:	---
Handle	
Colours:	Standard color: white, brown, silver Optional color: stainless steel, old gold, woodwork color

Handle model:	Handle on a long backplate made of high quality aluminum.
Insert	
Insert type:	Construction insert
Lock	
Lock type:	1-point locking system with a classic latch-bolt mechanism
Sash size	
Min. sash width:	900 mm
Max. sash width:	1250 mm
Min. sash height:	2050 mm
Max. sash height:	2400 mm
Max. sash weight:	180 kg
Max. sash area:	---