

# DPQ-82 AL



## Specifications

Thermal efficiency	
U <sub>w</sub> *: Coefficient value for reference design	0,77 W/m <sup>2</sup> K
*:	reference window 1230 x 1480 mm
Profile	
Profile name:	DPQ-82 AL
Installation depth:	87 mm
Number of chambers:	7
Thermal break:	---
Number of seals:	3
Glass	
Glazing package:	4/18/4/18/4
U <sub>g</sub> value:	0,5 W/m <sup>2</sup> K
Package thickness:	48 mm
Sound insulation of available glazing:	---
Fitting	
Type:	---
Hinges:	surface-mounted

Anti-Theft protection:	2 anti-theft latches
Micro-ventilation:	yes
Other:	---
<b>Handle</b>	
Colours:	---
Handle model:	1006
<b>Dimensions</b>	
Maximum window width - single sash:	1500 mm
Maximum window height - single sash:	2575 mm
Maximum window width - double sash with a movable post:	2085 mm
Maximum window height - double sash with a movable post:	2480 mm
Maximum sash area:	2,25 m <sup>2</sup>
Maximum size of fixed glazing (when using a special glass, maximum area of 7 m2 and weight of 250 kg):	3500 x 2900 mm or 2900 x 3500 mm

## Photos

