



Specifications

Thermal efficiency	
U _w *: Coefficient value for reference design	0,9 W/m ² K
*:	reference window 1230 x 1480 mm
Profile	
Profile name:	DPB-73
Installation depth:	73 mm
Number of chambers:	5
Thermal break:	none
Number of seals:	2
Glass	
Glazing package:	4/16/4/16/4
U _g value:	0,5 W/m ² K
Package thickness:	44 mm
Sound insulation of available glazing:	---
Fitting	
Type:	---
Hinges:	surface-mounted

Anti-Theft protection:	none
Micro-ventilation:	yes
Other:	---
Handle	
Colours:	---
Handle model:	1006
DPB series dimensions (white profile)	
Maximum window width – single sash:	1575 mm
Maximum window height – single sash:	2465 mm
Maximum window width – double sash with a movable post:	1960 mm
Maximum window height – double sash with a movable post:	2465 mm
Maximum sash area:	2,25 m ²
Maximum size of fixed glazing (when using a special glass, maximum area of 7 m ² and weight of 250 kg):	3500 x 2900 mm or 2900 x 3500 mm
DPB series dimensions (veneered profile)	
Maximum window width – single sash:	1475 mm
Maximum window height – single sash:	2435 mm
Maximum window width – double sash with a movable post:	1890 mm
Maximum window height – double sash with a movable post:	2350 mm
Maximum sash area:	2,05 m ²
Maximum size of fixed glazing (when using a special glass, maximum area of 7 m ² and weight of 250 kg):	3500 x 2900 mm or 2900 x 3500 mm

Photos

