



Specifications

Thermal efficiency	
U _w *: Coefficient value for reference design	1,4 W/m ² K
*:	reference construction 2460 mm x 2180 mm
Profile	
Profile name:	DA-51
Installation depth:	3-chamber profile, Sash: 51 mm Frame: - double track frame: 118 [mm] - double track frame with threshold flush aligned as an option: 125 [mm]) - triple track frame: 184 [mm] - triple track frame with threshold flush aligned as an option: 192 [mm]) - monorail: 142 [mm]
Number of chambers:	3
Thermal break:	Thermal breaks 26 mm made of fiber glass reinforced by polyamide
Number of seals:	2 perimeter seals
Glass	
Glazing package:	4ESG/12Ar/4ESG/12Ar/4ESG
U _g value:	0,7 W/m ² K
Package thickness:	8 to 36 mm - sash 20 to 60 mm fixed surfaces in monorail constructions
Sound insulation of available glazing:	R _w : from 31 to 40dB
Fitting	
Type:	Track with inox rollers provides lifting capacity to 250 kg
Hinges:	n/a
Anti-Theft protection:	n/a
Micro-ventilation:	n/a
Other:	n/a
Handle	
Colours:	Standard colour: white, brown, silver Optional colour: RAL palette

Handle model:	Handle on long handle plate, made of aluminium
Sash size	
Min. sash width:	600 mm
Max. sash width:	2600 mm
Min. sash height:	520 mm
Max. sash height:	2800 mm
Max. sash weight:	250 kg
Max. sash area:	---